

LUXUM LED REMOVING DARKNESS



KEY ADVANTAGES



LED LUMINOUS SOURCE



LED DRIVER



High-end Mean Well LED driver, optimal stability, performance and lifespan.





NEVER BEFORE POSSIBLE

LUMILEDS

LED MODULE

Exquisite design with powerful thermal



dissipation and IP68 waterproof performance.



MAXIMUM ENERGY SAVINGS

Equipped with high energy LEDs and remote management options for a dramatic reduction in energy consumption.



WIDE RANGES OF PHOTOMETRIC **DISTRIBUTION**


Specifically developed for lighting spaces where the well-being and safety of people using the environments are essential.

FUTUREPROOF

Modular system makes maintenance easier. Replace the module without change the whole light.

IP66 IK10

XTREME **LUMINAIRE DESIGN**



deposition.

increased heat dissipation speed and solved the problem of dust

Overview

An elegant design with the Lighting CCPL-LS LED modules combined with highly efficient Philips LED and highly reliable Mean Well LED Driver

The CCPL-LSxB LED street lights have a high luminous efficiency and better service life. Provide 5 years warranty on luminaire.


Color

Silver Grey

Easy Installation








Innovative pole fitter design achieve the horizontal and vertical installation features.

It also has 0-15° adjustable function for each installation direction.


DETAILED FEATURES




Optics, available as an option (required)




Applications: Single Driveway | Walkway /Cycleway | Branch Road



Applications:
Two Driveway | Driveway Entrance | Urban Road



Applications: Three Driveway | Highway | Parking Lot /Area



Applications: Parking Lot | Square | Area



Professional lens design, suitable for various applications.



Luminaire body is fixed by two M8x16 fortified stainless steel screws.



Rational clamshell design for wiring compartment, sturdy and durable.



Use stainless steel screws for whole luminaire, no corrosion worries.



Use German W/A GDC connectors for output wiring, safe, convenient & fast.



Innovative pluggable connector, clean & efficient.




Full aluminum made, sufficient heat dissipation area.



CHARACTERISTICS




DIMENSION DATA



Number of Modules	1	2	3	4	5	6	7
"L" Length	431 mm	504 mm	577 mm	650 mm	723 mm	796 mm	869 mm
	17.0"	19.8"	22.7"	25.6"	28.5"	31.3"	34.2"
Weight	5.3 kg	6.1 kg	7.3 kg	8.2 kg	9.0 kg	9.9 kg	10.8 kg
	11.7 lbs.	13.4 lbs.	16.1 lbs.	18.1 lbs.	19.8 lbs.	21.8 lbs.	23.8 lbs.

Pole fitting diameter: 60mm

PACKAGING DATA



Number of Modules	1	2	3	4	5	6	7
"L" Length	480 mm	555 mm	630 mm	705 mm	780 mm	855 mm	930 mm
	18.9"	21.9"	24.8"	27.8″	30.7"	33.7"	36.6"
Weight	6.3 kg	7.3 kg	8.6 kg	9.6 kg	10.6 kg	11.6 kg	12.6 kg
	13.9 lbs.	16.1 lbs.	19.0 lbs.	21.2 lbs.	23.4 lbs.	25.6 lbs.	27.8 lbs.

Product	Power	Lumen Output (+/- 5%)	Recomended Mounting Height	Replacement of standard	Important Parameters		
CCDL LC1D	30W	3942lumens	4-7 m	HPS 70W	Input Voltage	100-240V /277V AC 50/60Hz	
CCPL-LS1B	50W	6793lumens	5-8 m	HPS 130W	Operating Temperature	-40 °C to +50 °C	
	60W	8117lumens	6-10 m	HPS 150W	5 . (25)		
CCPL-LS602B	80W	10057lumens	7-11 m	HPS 200W	Power Factor (PF)	> 0.95	
	100W	11525lumens	8-12 m	HPS 250W	Total Harmonic Distortion (THD)	< 20%	
CCPL-LS1203B	120W	15066lumens	9-14 m	HPS 300W	Optic (option)	1M,2M,3M,5S	
	150W	17305lumens	10-15 m	HPS 400W	CRI	Minimum 80 CRI	
	180W	21618lumens	11-16 m	HPS 450W		3000K 4000K	
CCPL-LS1804B	200W	23205lumens	11-17 m	HPS 500W	ССТ	5000K 5700K	
CCPL-LS5B	240W	28800lumens	12-18 m	HPS 600W	Rating	IP66, IK10	
CCPL-LS6B	300W	35100lumens	14-20 m	HPS 750W	Heat Radiator	Anodized Aluminum	
CCPL-LS7B	320W	37760lumens	15-21 m	HPS 800W	Lens	PC (UV resistance)	

The 60W, 120W and 180W are stocked products. Other wattages are available on request.

All stocked products are supplied with colour temperature (CCT) 5000K

CERTIFICATION


























ASSEMBLE STEPS








PHOTO CONTROL (OPTIONAL)

The PHOTO CONTROL is a special order, available on request.

Telephone: 02071 182 182 International: +44 2071 182 182 Email: contact@luxum.co.uk Web: www.luxum.co.uk LUXUM LED REMOVING DARKNESS

Design Technology Solutions